

In the claims:

Kindly cancel claims 12 and 15 and rewrite the subject matter as new claims 30 and 31, respectively, as follows:

30. In a star network having a plurality of N nodes interconnected by a plurality of links, with one of the nodes being the *hub* node h and the other nodes being $\{x_1, \dots, x_{N-1}\}$ *spoke nodes*, and being connected to the hub node by one of the links having W channels, where W is even, a method of configuring the nodes comprising:

- 65
- (a) dividing channels into two sets, with each set having $W/2$ channels, where the first set has channels numbered $\{0, \dots, W/2 - 1\}$ and the second set has channels numbered $\{W/2, \dots, W - 1\}$;
 - (b) configuring the hub node such that channel i on any one of the links may be connected to channel $w(i)$ on any of the links by a connection, where $w(i)$ equals $i + W/2$;
 - (c) assigning channels to the connection which traverses at most two of the links, wherein paths p_1, \dots, p_m traverse exactly two of the links and paths p_{m+1}, \dots, p_M traverse only one of the links, wherein the links are designated as links e_1, e_2, \dots, e_{N-1} such that for $i = 1, \dots, N - 1$, e_i is between nodes x_i and h ;
 - (d) identifying a path *incident* to the end nodes of the path;
 - (e) *directing* paths $\{p_1, \dots, p_m\}$ so that each path extends from one end node of the path to the other end node of the path, each spoke node having at most $W/2$ incident paths that are directed into the spoke node and at most $W/2$ incident paths that are directed out of the spoke node;
 - (f) identifying a free node that has at least one incident undirected path;
 - (g) directing the paths $\{p_1, \dots, p_m\}$ by using the following procedure:
 - i. if each link has exactly W paths from the set $\{p_1, \dots, p_M\}$ that traverse the link then let $R = M$; otherwise, construct additional

paths $p_{M+1}, p_{M+2}, \dots, p_R$ in the star network so that for each link, there are exactly W paths from the set $\{p_1, \dots, p_R\}$ that traverse the link;

ii. considering all paths $\{p_1, \dots, p_R\}$ *undirected*, and

iii. as long as there is a free node,

A. starting from a free node, x_i , and traversing an undirected incident path (from the set $\{p_1, \dots, p_R\}$) to the other end node, and directing the path in the direction of the traversal,

B. starting from the other end node, traversing an undirected incident path (from the set $\{p_1, \dots, p_R\}$) to the next end node, and directing the path in the direction of the traversal, and

C. keep traversing undirected paths (and directing the traversed paths) until x_i is reached;

(h) creating a bipartite graph G which has two sets of vertices $\{u_1, \dots, u_{N-1}\}$ and $\{v_1, \dots, v_{N-1}\}$ and has edges $\{b_1, \dots, b_m\}$ such that for $i = 1, \dots, m$, b_i is between u_j and v_k if path p_i is directed so that it traverses link e_j and then e_k ;

(i) assigning a number from the first set of channels $\{0, \dots, W/2 - 1\}$ to the edges of graph G such that at any vertex in graph G has all of its incident edges assigned to a distinct number of the first set, and denoting the number assigned to each edge b_i by $q(b_i)$; and

(j) for $i = 1, \dots, m$, assigning channels to p_i where

i. the channels are $q(b_i)$ from link e_j and $w(q(b_i))$ from link e_k where j and k are such that u_j and v_k are the end vertices of b_i , where $w(i) = i + W/2$, and

(k) for $i = 1, 2, \dots, N - 1$, assigned distinct channels to all paths from the set $\{p_{m+1}, \dots, p_M\}$ that traverse the link e_i such that the channels are not already assigned to paths from $\{p_1, \dots, p_m\}$.

31. In a network consisting of N nodes and E links e_1, e_2, \dots, e_E , wherein each link between nodes is a multichannel multiplexed link, consisting of W channels $\{0, 1, \dots, W-1\}$, where W is even, a method of configuring the nodes in the network comprising:

- (a) grouping the channels into two sets, $\{0, \dots, W/2-1\}$ and $\{W/2, \dots, W-1\}$;
- (b) at each node, for $i = 0, 1, \dots, W/2-1$, connecting channel i on one link to channel $w(i)$ on all the other links incident on that node, where $w(i) = i + W/2$;
- (c) assigning channels to connections $1, 2, \dots, m$ using paths p_1, \dots, p_m , wherein each of the paths traverses at most two of the links, where no two connections traversing the same one of the links are assigned to the same channel on the one link;
- (d) creating an equivalent star network with $E + 1$ nodes with the E nodes e'_1, e'_2, \dots, e'_E corresponding to the edges in the original network and the remaining node h being the hub node; and
- (e) creating an equivalent set of connections in the star network p'_1, p'_2, \dots, p'_m such that:
 - i. if connection p_i uses link e_j in the original network then connection p'_i uses the link between nodes e'_j and h in the star network,
 - ii. if connection p_i uses links e_j and e_k in the original network then connection p'_i uses the following two links in the star network: the link between nodes e'_j and h and the link between nodes e'_k and h ,
 - iii. assigning channels to the p'_i according to step (c) and assigning the same set of channels to p_i as to p'_i , and
 - iv. assigning channels to the set of paths p'_1, \dots, p'_m such that for $i = 1, 2, \dots, m$ if p'_i is assigned channel c on the link between nodes e'_j and h and is also assigned channel c' on the link between nodes h and e'_k in the star

b5 network then c and c' are the channels assigned to path p_i for links e_j and e_k respectively.

Kindly amend claims 11, 13, 14 and 16 as follows:

11. (Amended) In a star network having a plurality of N nodes interconnected by a plurality of links, with one of the nodes being the *hub* node h and the other of the nodes being $\{x_1, \dots, x_{N-1}\}$ *spoke nodes* connected to the hub node by links each having a plurality of W channels going into the hub node h and out of the hub node h , where W is even, a method of configuring the nodes comprising:

b1 (a) dividing the channels into two sets, with each set having $W/2$ channels, where the first set has channels numbered $\{0, \dots, W/2 - 1\}$ and the second set has channels numbered $\{W/2, \dots, W - 1\}$; and

(b) configuring the hub node such that channel i on any one of the links may be connected to channel $w(i)$ on any of the links, where $w(i)$ equals $i + W/2$ and where i is no greater than W .

13. (Amended) In a star network having N nodes with one of the nodes a hub node, wherein each of the other of the nodes is connected to the hub node by a multichannel link having W channels, where W is an even integer, a star network configured as follows:

b2 the hub node configured such that channel i on any one of the links may be connected to channel $w(i)$ on any other of the links, where $w(i) = (i + W/2)$ and where i is no greater than W .

14. (Amended) In a network consisting of N nodes and E links e_1, e_2, \dots, e_E , wherein N and E are any integer and wherein each link between nodes is a multichannel multiplexed link, consisting of W channels $\{0, 1, \dots, W-1\}$, where W is even, a method of configuring the nodes in the network comprising:

b2 (a) grouping channels into two sets, $\{0, \dots, W/2-1\}$ and $\{W/2, \dots, W-1\}$; and

(b) at each node, for $i = 0, 1, \dots, W/2-1$, connecting channel i on one link to channel $w(i)$ on all the other links incident on that node, where $w(i) = i + W/2$.

16. (Amended) A network having N nodes and E links for interconnecting the nodes where N and E are any integer, where each link is a multichannel multiplexed link having W channels, and where W is even, a network configured as follows:

b3 each node, for $i = 0, 1, \dots, W/2-1$, channel i on one incident link connected to channel $w(i)$ on all other incident links of each node, where $w(i) = i + W/2$.

Kindly amend claims 17-29 as follows:

17. (Amended) In a star communication network comprising a hub node and a plurality of spoke nodes and comprising a plurality of links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of W channels into the hub node and out of the hub node, a method of configuring the network comprising the steps of:

b4 limiting the W channels to an even number;

dividing the W channels into a first group and a second group in each of the links;

connecting each channel of the first group of one of the links to one channel of the second group of each of the links other than the one link; and

assigning no more than W channels to the transmission of data along any of the links, (whereby the efficiency of the configuring is improved.)

18. (Amended) A method, as claimed in claim 17, and further comprising the step of assigning routes to the channels which traverse at most two of the links.

19. (Amended) A method, as claimed in claim 17, wherein the step of connecting comprises the step of connecting each channel $i = 0, 1, \dots, W/2 - 1$ of a first one of the links through the hub node to channel $w(i)$ on each of the links other than the first link where $w(i) = i + W/2$.

20. (Amended) A star communication network comprising in combination:

a plurality of spoke nodes;

a hub node; and

links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of W channels into the hub node and out of the hub node, the channels being divided into a first group and a second group where W is even, the hub node connecting each channel of the first group of one of the links to one channel of the second group of each of the links other than the one link.

21. (Amended) A network, as claimed in claim 20, wherein each link comprises no more than W channels.

22. (Amended) A network, as claimed in claim 20, comprising routes arranged to carry the W channels, wherein the routes traverse at most two of the links.

23. (Amended) A network, as claimed in claim 20, wherein each channel $i = 0, 1, \dots, W/2 - 1$ of the one link is connected through the hub node to channel $w(i)$ on all of the links other than the one link where $w(i) = i + W/2$.

24. (Amended) In a star communication network comprising a hub node and a plurality of spoke nodes and comprising links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of W channels into the hub node and out of the hub node, a method of configuring the network comprising the steps of:

assigning no more than W channels to the transmission of data along any of the links; and

connecting each channel of a first one of the links to no more than two channels of a second one of the links through the hub node, (whereby the efficiency of the configuring is improved.)

25. (Amended) A star communication network comprising in combination:

a plurality of spoke nodes;

a hub node; and

links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of W channels into the hub node and out of the hub node, the hub node connecting each channel of a first one of the links to no more than two channels of a second one of the links through the hub node.

26. (Amended) In a star communication network comprising a hub node and a plurality of spoke nodes and comprising links coupled between the hub node and the

plurality of spoke nodes, each link being arranged to carry a plurality of no more than W channels into the hub node and out of the hub node, a method of configuring the network comprising the steps of:

assigning no more than W channels to the transmission of data along any of the links; and

connecting each channel of a first one of the links to no more than a second channel of a second one of the links through the hub node, where the second channel is different from the first channel of the second one of the links.

27. (Amended) A star communication network comprising in combination:

a plurality of spoke nodes;

a hub node; and

links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of no more than W channels into the hub node and out of the hub node, the hub node connecting each channel of a first one of the links to no more than a second channel of a second one of the links through the hub node, where the second channel is different from the first channel of the second one of the links.

28. (Amended) A method of proposing a star network comprising:

proposing a network comprising a hub node and a plurality of spoke nodes;

proposing links coupled between the hub node and the plurality of spoke nodes, each link being arranged to carry a plurality of W channels into the hub node and out of the hub node, the channels being divided into a first group and a second group where W is even; and